



SPECIFICATIONS

TSF® 200



Appliance for integrating in existing infrastructure
Part of the Trusted Security Foundation® (TSF®) product suite

Configuration	<p>Rackmount Appliance</p> <ul style="list-style-type: none"> • Dimensions: 1RU - H: 4.28 cm (1.69”), W: 48.20 cm (18.98”), D: 80.85 cm (31.83”) • Weight: 22 kgs (48.50 lbs) • Power Supply: 1RU - Dual, redundant, hot-swappable, 750W • Support for both centralized and distributed deployment topologies to suit any availability or performance requirements • Support for running multiple Virtual Machines (VMs)
Replication	<ul style="list-style-type: none"> • Secure replication of policies and managed cryptographic objects — up to 16 nodes per replication group • Supports both synchronous and asynchronous replication
Random Number Generation	<ul style="list-style-type: none"> • Optional quantum random number generator (QRNG) PCIe card supporting true random key generation • Up to 1 Gbit/sec true random stream • Conforms with NIST SP 800-90A, B, and C (draft) • Satisfies NIST SP 800-22 (NIST STS) and Dieharder tests • Fully independent output for each user, full audit trail from hardware to consumer • RESTful API support for delivering random data
Cryptography & Security	<ul style="list-style-type: none"> • Supports non-embedded FIPS 140-2 Level 3 cryptographic module • Supports one-time pad, symmetric key and asymmetric key ciphers, key derivation, random objects, certifications and some cryptographic operations • Granular, hierarchical and auditable access control • Event log, audit log, date and time of transaction, management and user reports • Thousands of end-client systems per node, 8,000 key requests/minute per node • Attended or unattended secure startup
Standards & Interoperability	<ul style="list-style-type: none"> • OASIS KMIP: Conformant with standards 1.0/1.1/1.2/1.3/1.4/2.0 • Fully implements all requirements in NIST SP 800-57 Part 1 • Common Criteria EAL 2 certified • Supports PKCS#11 over KMIP
Administration & Management	<ul style="list-style-type: none"> • Web (HTTPS) or command-line (SSH) management interfaces • Purpose-built QRE secure operating system • Delivered with qClient™ 100